



Sensormatic Ultra•Post®

Ultra•Post® is a cornerstone of the Sensormatic detection portfolio, providing high performance anti-shoplifting protection to retailers around the globe. Affordable, effective and easy to maintain the Ultra•Post® remains a popular choice among leading retailers to help protect their merchandise and profits.

With added functionality and improved aesthetics, the Ultra•Post® IV feature-rich design offers retailers the added benefits of SmartEAS® networking connectivity, people counting ready options and synchronization capabilities. With an updated look and color change, Ultra•Post® IV provides an aesthetic solution suitable for any retail environment -- from malls to stand alone stores.

Designed to protect a variety of exit openings, this versatile system covers almost any exit width. A single pedestal can protect a 0.9m (3ft), while two pedestals spaced 1.8m (6ft) apart can cover an exit up to 3.6m (12ft). The spacing flexibility makes Ultra•Post® IV an ideal solution for a variety of retail footprints.

Benefits

Flexible Configurations. The Ultra•Post® IV can be tailored for a variety of store exits, offering up to 3.6m (12ft) of detection coverage.

Easy Installation. This system contains all the components necessary to operate as a stand-alone self-contained pedestal, with integrated power supply to allow for easy, cost effective installation. Ultra•Post IV has the capability to operate via a standard wall outlet or through the traditional hardwiring method.

High-performance. Leading Ultra•Max® technology ensures system reliability, capable of detecting security tags inside foil-lined bags, metal shopping carts or tagged protects containing non-ferrous metal.

Low Profile Attractive Design. The narrow architecture and rich color scheme ensure the Ultra•Post® IV will blend into any retail environment.

Integrated People Counting Option. Helps retailers understand customer traffic flow at a store, division and corporate level, detailing necessary information for managing staffing, merchandising and operations.

Options

Ultra•Post[®] IV offers a variety of options; for more information on these options please contact your sales representative.

- Traffic Flow Sensors (People Counting Sensors)
- Digital Remote Alarm
- LDM and UltraLink[®]
- Ranger receivers
- Satellite receivers

Specifications

Electrical

Power Supply (Switched Mode Transmitter)

Primary Input..... 100-120Vac or
220-240Vac
@ 50-60Hz

Primary Power Fuse 2.5A, 250V, 5x20,
slow-blow, hi-breakage

Current Draw 2.0A peak

Input Power <180W

Transmitter (Switched Mode Transmitter)

Outputs..... 1 port (two antennas,
multiplexed)

Operating Frequency 58kHz (±200Hz)

Transmit Burst Duration..... 1.6ms

Transmit Current 16A peak

Burst Repetition Rate:

Based on 50Hz ac 37.5Hz (Normal)
75Hz (Validation)

Based on 60Hz ac 45Hz (Normal)
90Hz (Validation)

Transmit Coil Resistance 1.6 ohms (±5%)

Product Codes

ZS1012-P UP4 Primary Antenna
Non-EU (Single)

ZS1012-S UP4 Secondary
Antenna Non-EU

ZPUE-PEDMTG Hilt Bolt Mounting
Kit

ZA1012-1 UP4 Single System
Non-EU

ZPUP-PEOPLECNTR..... UP4 People Counting
Kit

Additional Information

For more information about the Sensormatic Ultra•Post[®] IV, please contact your ADT sales representative or visit www.Sensormatic.com.